NSN 6625-00-407-6835

Multimeter - Page 1 of 2

Power Source:

External



View Online at https://aerobasegroup.com/nsn/6625-00-407-6835

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
1500.0
Overall Length:
2.031 inches
Mounting Hole Diameter:
0.116 inches
Scale Division Quantity:
20 single indicator all ranges
Overall Diameter:
2.700 inches
Environmental Protection:
Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
water resistant
Mounting Bolt Circle Diameter:
2.440 inches
Furnished Items And Quantity:
Nut 7; shunt wire 1; lockwasher 5
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
50.0 millivolts
Dial Scale Marking Color:
White single indicator all ranges
Accuracy In Percent:
-2.0 to 2.0 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
1.406 inches
Meter Body Diameter Behind Mounting Flange:
2.031 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
Black single indicator all ranges
Pointer Color:
White single indicator all ranges

NSN 6625-00-407-6835 Multimeter - Page 2 of 2



Mounting Facility Type And Quantity:
3 screw and 3 unthreaded hole
Scale Graduation Type:
Linear single indicator all ranges
Measurement Range:
+0.0 to 50.0 volts single indicator 2nd range
Scale Selection Method:
Terminal
Features Provided:
External shunting and zero adjuster
Criticality Code Justification:
Feat Feat
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Special Features:
Critical application-hawk: improved platoon command post, hawk (an/msw-14) and information coord central, hawk (e0725) (an/tpx-46
an/msq-111); hawk mim-23 missile
Special Markings:
On back, sealed do not open; ruggedized
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint
Special Test Features:
Complies with mil-m-10304
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A310a0