

View Online at <https://aerobasegroup.com/nsn/6625-00-411-9606>

Circuit Current For Which Designed:

Dc

Overall Length:

3.281 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.766 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.766 inches

Overall Height:

3.625 inches

Overall Width:

3.625 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Red and white single indicator all ranges

Accuracy In Percent:

-0.5 to 0.5 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.875 inches

Meter Body Diameter Behind Mounting Flange:

2.750 inches

Movement Type:

Moving magnet

Background Color:

Black single indicator all ranges

Pointer Color:

White single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 unthreaded hole

Measurement Range:

+26.0 to 29.5 volts, dc single indicator 2nd range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

6 threaded stud

Material:

Plastic phenolic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Cadmium

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0