## NSN 6625-00-412-4816

Ammeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-412-4816

### **Circuit Current For Which Designed:**

Dc

#### **Overall Length:**

2.185 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Length:

1.880 inches

#### Center To Center Distance Between Mounting Facilities Parallel To Width:

1.880 inches

#### **Overall Height:**

2.470 inches

#### **Overall Width:**

2.470 inches

#### Scale Division Quantity:

50 single indicator single range

#### **Mounting Stud Length:**

0.500 inches

#### Indicator Type:

Dial w/pointer

#### Installation Design:

Panel

#### Mounting Arrangement Style:

Four hole/stud rectangular/square

#### **Dial Scale Marking Color:**

Black single indicator single range

#### Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

#### Meter Depth Behind Mounting Flange:

1.060 inches

#### Meter Body Diameter Behind Mounting Flange:

2.170 inches

#### **Background Color:**

White single indicator single range

#### **Pointer Color:**

Black single indicator single range

#### **Power Source:**

External

#### Mounting Facility Type And Quantity:

4 threaded stud

#### Scale Graduation Type:

Linear single indicator single range

#### Measurement Range:

+0.0/+250.0 milliamperes, dc single indicator single range

# NSN 6625-00-412-4816

Ammeter - Page 2 of 2

Μ	ounting Stud Diameter:
0.	112 inches
S	cale Selection Method:
Te	erminal
Fe	eatures Provided:
Ze	ero adjuster
C	ircuit Attachment Method And Quantity:
2	threaded stud
Μ	aterial:
ΡI	lastic
N	uclear Hardness Critical Feature:
N	onhardened
St	tyle Designator:
R	ectangular flush mtg
F	sc Application Data:
Te	est set, elect. Equip.
S	helf Life:
N	/a
U	nit Of Measure:
D	emilitarization:
N	0
Fi	iig:
A:	310a0

