

View Online at <https://aerobasegroup.com/nsn/6625-00-421-8047>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

1.630 inches

**Overall Height:**

1.750 inches

**Overall Width:**

1.750 inches

**Scale Division Quantity:**

20 single indicator single range

**Environmental Protection:**

Shock resistant and vibration resistant and water resistant

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Sensitivity Rating:**

1000.0 ohms per volt

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator single range

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

1.000 inches

**Meter Body Diameter Behind Mounting Flange:**

1.422 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

1 ring and 1 threaded body

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0 to 40.0 volts, dc single indicator single range

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Features:**

Ruggedized

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Special Test Features:**

Meets requirements of ansi c39.1

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0