

View Online at <https://aerobasegroup.com/nsn/6625-00-422-2691>

Circuit Current For Which Designed:

Ac or dc

Overall Length:

8.750 inches

Overall Height:

6.062 inches

Overall Width:

5.125 inches

Scale Division Quantity:

64 single indicator 4th range

Frequency Rating:

Between 48.0 hertz and 440.0 hertz

Furnished Items And Quantity:

Power cord 1

Indicator Type:

Dial w/pointer

Installation Design:

Bench

Frequency Response Range:

+0.010 to 1000.000 kilohertz

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Background Color:

White single indicator all ranges

Pointer Color:

Red single indicator all ranges

Power Source:

External or internal

Scale Graduation Type:

Nonlinear single indicator 2nd range

Measurement Range:

-10.0 to 0.0 decibels above or below one milliwatt single indicator 1st range

Scale Selection Method:

Switch

Features Provided:

Internal battery accommodation and knife edge pointer and mirror scale and portable and zero adjuster

Circuit Attachment Method And Quantity:

3 banana jack

Operating Voltage Rating In Volts:

115.0 ac and 230.0 ac and 22.5 dc

Special Features:

Two knobs; three slide switches; one chassis ground terminal; one line selector; one battery line

Special Markings:

Range: ac only; 0.01, 0.03; 0.1, 0.3, 1.0, 3.0, 10.0, 30.0, 100.0, 300.0; dc only; 1000.0; range: x10, x100, x1k, x10k, x100k, x1m, x10m;
function: off, batt 1.5 min, dcv +, dcv -, ohm, acv

Material:

Aluminum and plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular or square

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0