

View Online at <https://aerobasegroup.com/nsn/6625-00-431-9242>

Circuit Current For Which Designed:

Ac

Overall Length:

5.062 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

5.969 inches

Overall Height:

6.469 inches

Overall Width:

6.469 inches

Scale Division Quantity:

65 single indicator single range

Mounting Stud Length:

0.594 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Frequency Response Range:

+350.000 to 1000.000 hertz

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0 to 1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

3.437 inches

Meter Body Width Behind Mounting Flange:

5.562 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+350.0 to 1000.0 hertz single indicator single range

Mounting Stud Diameter:

0.190 inches

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

5.562 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Operating Voltage Rating In Volts:

120.0 ac

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0