## NSN 6625-00-432-7312

Modulation Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-432-7312

Circuit Current For Which Designed:
Ac
Overall Length:
19.000 inches
Overall Height:
14.625 inches
Overall Width:
10.500 inches
Frequency Rating:
Between 50.0 hertz and 420.0 hertz
Indicator Type:
Dial w/pointer
Installation Design:
Bench
Sensitivity Rating:
0.5 volts
Dial Scale Marking Color:
Black single indicator all ranges
Accuracy In Percent:
-10.0/+10.0 at full scale single indicator all ranges
Background Color:
White single indicator all ranges
Pointer Color:
Black single indicator all ranges
Power Source:
External
Scale Graduation Type:
Linear single indicator all ranges
Measurement Range:
+0.0/+50.0 kilohertz single indicator 2nd range
Scale Selection Method:
Terminal
Features Provided:
Portable
Circuit Attachment Method And Quantity:
2 binding post
Phase:
Single Special Features:
Special Features:  Measures deviation over a range from 0 to 1000 kbz at rf frog from 20 to 1000 mbz
Measures deviation over a range from 0 to 1000 khz at rf freq from 20 to 1000 mhz
Material:
Wood

## NSN 6625-00-432-7312

Modulation Meter - Page 2 of 2



<b>Nuclear Hardness Critical Feature:</b>
Nonhardened
Surface Treatment:
Paint
Style Designator:
Rectangular or square
Fsc Application Data:
Test set, electronic equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

**Fiig:** A310a0