## NSN 6625-00-432-7904

Multimovement Electrical Meter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-00-432-7904

## **Special Features:**

Movement data, not ac, dc, 1, 50 mv sensitivity, porm 2 pct accuracy at full scale reading, not rf type, not ac, dc, 1, not rated for sensitivity, porm 0.7 v accuracy at full scale reading, not rf type; panel type, style no.2, sect c, rdg 27, dim.Data, rdg 27, 1.342 in.Max depth of meter to mtg flange, 2.375 in.Lg of mtg flange, 2.375 in.W of mtg flange, 2.255 in.Dia of meter body, not portable type; scale data, amp, 450 to 0 top to bottom range, graduation data, linear, 18 scale div not nonlinear, volt, 33 to 15 top to bottom range, graduation data, linear, 18 scale div, not nonlinear; mtg data, flange mtd, four 0.170 in.Dia mtg holes spaced 90 degrees apart on 1.313 in.Radius; terminal data, 4, screw-stud type, no.10/0.190 in./-32 nf thd, 0.688 in.Lg; components and accessories data, shunt, 1, ms, part no.Ms91587-6; no special features **Shelf Life:** 

N/a

Unit Of Measure:

--

## **Demilitarization:**

No

Fiig:

A310a0