

View Online at <https://aerobasegroup.com/nsn/6625-00-433-4209>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

1000.0

**Overall Length:**

1.251 inches

**Overall Diameter:**

1.250 inches

**Environmental Protection:**

Vibration resistant

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Sensitivity Rating:**

200.0 microamperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-3.000 to 3.000 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

0.901 inches

**Meter Body Diameter Behind Mounting Flange:**

1.000 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

1 collar and 1 threaded body

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

+0.0 to 50.0 watts single indicator single range

**Scale Selection Method:**

Terminal

**Features Provided:**

Magnetic shield and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder lug

**Special Features:**

Ruggedized

**Material:**

Aluminum

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Anodize and enamel semigloss

**Special Test Features:**

1200 ohms resistance

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiiig:**

A310a0