

View Online at <https://aerobasegroup.com/nsn/6625-00-434-1545>

**Circuit Current For Which Designed:**

Dc

**Scale Division Quantity:**

80 single indicator 1st range

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

100.0 microamperes

**Dial Scale Marking Color:**

Pink and white single indicator 2nd range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator all ranges

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

Black single indicator all ranges

**Pointer Color:**

Red single indicator all ranges

**Scale Marking:**

Top scale: 380, 390, 400, 410, 420; middle scale: 111, 113, 115, 117, 119; bot scale: 26, 27, 28, 29

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Linear single indicator all ranges

**Features Provided:**

Luminous scale marking and mirror scale and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mntg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0