

View Online at <https://aerobasegroup.com/nsn/6625-00-434-1545>

Circuit Current For Which Designed:

Dc

Scale Division Quantity:

80 single indicator 1st range

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

100.0 microamperes

Dial Scale Marking Color:

Pink and white single indicator 2nd range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator all ranges

Pointer Color:

Red single indicator all ranges

Scale Marking:

Top scale: 380, 390, 400, 410, 420; middle scale: 111, 113, 115, 117, 119; bot scale: 26, 27, 28, 29

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator all ranges

Features Provided:

Luminous scale marking and mirror scale and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mntg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0