

View Online at <https://aerobasegroup.com/nsn/6625-00-434-1671>

Circuit Current For Which Designed:

Dc

Overall Length:

2.000 inches

Mounting Hole Diameter:

Between 0.143 inches and 0.157 inches

Overall Diameter:

3.500 inches

Environmental Protection:

Shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

3.160 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.200 inches

Meter Body Diameter Behind Mounting Flange:

2.670 inches

Movement Type:

Moving coil, permanent magnet

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Measurement Range:

+0.0 to 300.0 volts, dc single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0