

View Online at <https://aerobasegroup.com/nsn/6625-00-437-3721>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

2.130 inches

Scale Division Quantity:

4 all indicators all ranges

Mounting Stud Length:

Between 0.450 inches and 0.500 inches

Overall Diameter:

2.700 inches

Environmental Protection:

Watertight

Mounting Bolt Circle Diameter:

2.440 inches

Furnished Items And Quantity:

Mtg hdw 3; gasket 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

500.0 microamperes

Dial Scale Marking Color:

Black all indicators all ranges

Accuracy In Percent:

-5.0/+5.0 at full scale all indicators all ranges

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.410 inches

Meter Body Diameter Behind Mounting Flange:

2.210 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White all indicators all ranges

Pointer Color:

Black all indicators all ranges

Scale Marking:

First scale: train; second scale: elevation; graduation marks

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Linear all indicators all ranges

Mounting Stud Diameter:

0.112 inches

Features Provided:

Magnetic shield

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

4 pin

Special Features:

Elevation scale vertical to right on meter face; train scale horizontal upper meter face; scales meet upper right corner

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Resistance 1000 ohms

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0