

View Online at <https://aerobasegroup.com/nsn/6625-00-437-4931>

**Circuit Current For Which Designed:**

Dc

**Dielectric Withstanding Voltage In Volts:**

1500.0

**Overall Length:**

1.625 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 1.306 inches and 1.318 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

Between 1.309 inches and 1.315 inches

**Overall Height:**

Between 1.734 inches and 1.766 inches

**Overall Width:**

Between 1.734 inches and 1.766 inches

**Mounting Hole Diameter:**

Between 0.120 inches and 0.130 inches

**Scale Division Quantity:**

3 single indicator single range

**Environmental Protection:**

Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight

**Furnished Items And Quantity:**

Nut 4; washer 4

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

50.0 microamperes

**Dial Scale Marking Color:**

Green and orange and red and yellow single indicator single range

**Accuracy In Percent:**

-3.0 to 3.0 at full scale single indicator single range

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

1.000 inches

**Meter Body Diameter Behind Mounting Flange:**

1.510 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

L; n; h

**Mounting Facility Type And Quantity:**

4 screw and 4 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Features Provided:**

Luminous scale marking and magnetic shield and zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder stud

**Special Features:**

Ruggedized

**Special Markings:**

L to r first segment orange/yellow marked l; second segment green marked n; third segment red market h

**Material:**

Stainless steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel semigloss

**Special Test Features:**

Conforms to mil-m-10304/24, type mr13a5t5dcuar

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0