

View Online at <https://aerobasegroup.com/nsn/6625-00-437-6777>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

1.750 inches

Mounting Hole Diameter:

0.109 inches

Overall Diameter:

2.687 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Mounting Bolt Circle Diameter:

2.093 inches

Furnished Items And Quantity:

Shunt wire 1; nut 3; lockwasher 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

100.0 microamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.156 inches

Meter Body Diameter Behind Mounting Flange:

2.031 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Scale Marking:

Top scale, 0; 10; 35; 100; 150; bottom scale, 0; 36; 50; reverse; forward; forward

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator all ranges

Features Provided:

External shunting and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 screw and 2 solder lug

Special Features:

Ruggedized

Special Markings:

On back, sealed do not open; on front, forward; reverse; forward

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Cadmium and chromate

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0