

View Online at <https://aerobasegroup.com/nsn/6625-00-437-8195>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

2.337 inches

Overall Height:

0.500 inches

Overall Width:

1.250 inches

Mounting Hole Diameter:

0.149 inches

Environmental Protection:

Shock resistant and vibration resistant

Distance Between Mounting Facility Centers:

1.646 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Sensitivity Rating:

25.0 microamperes

Dial Scale Marking Color:

Black and green and red single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Bat.; rf

Mounting Facility Type And Quantity:

2 bracket and 2 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder stud

Special Features:

Ruggedized

Special Markings:

Red band 0 to 10 ua sensitivity; green band 10 to 25 ua sensitivity

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular surface mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0