

View Online at <https://aerobasegroup.com/nsn/6625-00-442-2809>

Circuit Current For Which Designed:

Dc

Overall Length:

3.521 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.408 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.721 inches

Overall Height:

1.021 inches

Overall Width:

2.680 inches

Mounting Hole Diameter:

0.144 inches

Scale Division Quantity:

4 single indicator single range

Environmental Protection:

Shock resistant and vibration resistant

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

100.0 microamperes

Dial Scale Marking Color:

Black single indicator single range and red single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

3.167 inches

Meter Body Width Behind Mounting Flange:

2.109 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Red single indicator single range

Scale Marking:

1.0; 0.1; 0; 0.1; 1.0; m rf; deviation; m mc p

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Meter Body Height Behind Mounting Flange:

1.017 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Ruggedized

Special Markings:

Red band 0.1 to 0.1

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0