

View Online at <https://aerobasegroup.com/nsn/6625-00-442-2809>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

3.521 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.408 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

0.721 inches

**Overall Height:**

1.021 inches

**Overall Width:**

2.680 inches

**Mounting Hole Diameter:**

0.144 inches

**Scale Division Quantity:**

4 single indicator single range

**Environmental Protection:**

Shock resistant and vibration resistant

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

100.0 microamperes

**Dial Scale Marking Color:**

Black single indicator single range and red single indicator single range

**Accuracy In Percent:**

-1.0/+1.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

3.167 inches

**Meter Body Width Behind Mounting Flange:**

2.109 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Red single indicator single range

**Scale Marking:**

1.0; 0.1; 0; 0.1; 1.0; m rf; deviation; m mc p

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Meter Body Height Behind Mounting Flange:**

1.017 inches

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder lug

**Special Features:**

Ruggedized

**Special Markings:**

Red band 0.1 to 0.1

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Surface Treatment:**

Enamel

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0