

View Online at <https://aerobasegroup.com/nsn/6625-00-443-1606>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

2000.0

Overall Length:

3.563 inches

Overall Height:

3.438 inches

Overall Width:

3.500 inches

Scale Division Quantity:

8 single indicator single range

Mounting Stud Length:

0.500 inches

Mounting Bolt Circle Diameter:

3.000 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Register Quantity:

1

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+380.000 to 420.000 kilohertz

Dial Scale Marking Color:

Black single indicator single range

Resonant Reed Quantity:

8

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

3.188 inches

Meter Body Diameter Behind Mounting Flange:

2.500 inches

Movement Type:

Vibrating reed

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+380.0 to 420.0 hertz single indicator single range

Mounting Stud Diameter:

0.125 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect.Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0