

View Online at <https://aerobasegroup.com/nsn/6625-00-443-9759>

Circuit Current For Which Designed:

Ac

Overall Length:

3.750 inches

Mounting Hole Diameter:

0.125 inches

Overall Diameter:

2.700 inches

Environmental Protection:

Dust resistant and humidity resistant and vibration resistant and water resistant

Mounting Bolt Circle Diameter:

2.440 inches

Furnished Items And Quantity:

Nut 3; lockwasher 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+55.000 to 550.000 hertz

Sensitivity Rating:

2.0 watts

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-0.6 to 0.6 at 1/2 scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

3.000 inches

Meter Body Diameter Behind Mounting Flange:

2.160 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

+23.5 to 28.5 volts, ac single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Conforms to mil-m-10304, except for physical size

Style Designator:

Round flush mtg

Supplementary Features:

Black finished hardware

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0