

View Online at <https://aerobasegroup.com/nsn/6625-00-444-4053>

Circuit Current For Which Designed:

Ac

Overall Length:

2.570 inches

Mounting Hole Diameter:

0.138 inches

Overall Diameter:

3.510 inches

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Mtg hdw 3; term. Hdw 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+0.000 to 400.000 hertz

Sensitivity Rating:

10000.0 ohms per volt

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-3.0 to 3.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.660 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

0, 2, 4, 6, 8, 10; extended lines at 0, just above 0, 2 and every five increments thereafter

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 screw and 2 solder lug

Special Features:

Ruggedized

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0