

View Online at <https://aerobasegroup.com/nsn/6625-00-444-6089>

Overall Length:

24.000 inches

Overall Height:

16.750 inches

Overall Width:

13.000 inches

Current Type:

Ac

Frequency Rating:

Between 50.0 hertz and 60.0 hertz

Accessory Components And Quantity:

2 adapters, 1 filter, 1 power cord, 4 probe

Voltage Rating:

Between 210.0 volts and 250.0 volts

Beam Quantity:

2

Mounting Method:

Carrying case

Accuracy Range In Percent:

-3.0/+3.0

Screen Size:

5 in.

Sweep Circuits:

Included

Generator Driven Feature:

Not included

Sweep Circuit Type:

Horizontal and vertical

Sweep Frequency Range:

+5000.0/+30000.0 hertz

Single Trigger Sweep Duration:

0.02 milliseconds

Trigger Sweep Voltage Amplitude Rating:

100.0 volts

Trigger Sweep Polarity Switch:

Included

Trigger Sweep Marker Intervals:

0.02 usec

Expanded Sweep:

Not provided

Amplifier Deflection Sensitivity Provision:

Provided

Vertical Deflection Sensitivity Voltage Rating:

7.0 volts rms per inch

Horizontal Deflection Sensitivity Voltage Rating:

30.0 volts any acceptable outside diameter

Input Intensity Modulation Feature:

Not provided

Plate Direct Connection Deflection Sensitivity Provision:

Not provided

Frequency Response Rating:

Not provided

Amplifier Input Impedance Rating Provision:

Not provided

Amplitude Calibrating Voltage Waveform:

Square wave

Calibrating Peak To Peak Amplitude:

100.0 volts

Measurement Range Quantity:

1

Measurement Range Steps:

0.2 mv to 100v in 18 steps

Calibrated Screen Scale:

Not included

Trace Storage Tube:

Not included

Camera Recording Device Accommodation:

Not provided

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-g