

View Online at <https://aerobasegroup.com/nsn/6625-00-445-8887>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

2.494 inches

Overall Height:

0.515 inches

Overall Width:

1.600 inches

Mounting Hole Diameter:

0.086 inches

Scale Division Quantity:

20 single indicator single range

Distance Between Mounting Facility Centers:

1.285 inches

Barrel Width:

1.600 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

Black single indicator single range and red single indicator single range

Accuracy In Percent:

-10.0/+10.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.260 inches

Meter Body Width Behind Mounting Flange:

1.600 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

Recording level; 0; 2; 4; 6; 8; 10

Mounting Facility Type And Quantity:

2 threaded hole

Scale Graduation Type:

Linear single indicator single range

Meter Body Height Behind Mounting Flange:

0.965 inches

Meter Barrel Depth:

1.622 inches

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Markings:

Scale and numerals black from 0 to 5 and red from 5.5 to 10

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg barrel, down

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0