

View Online at <https://aerobasegroup.com/nsn/6625-00-446-1699>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

2600.0

Overall Length:

2.067 inches

Mounting Hole Diameter:

Between 0.123 inches and 0.128 inches

Scale Division Quantity:

25 single indicator single range

Frequency Rating:

60.0 hertz

Overall Diameter:

2.750 inches

Environmental Protection:

Shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

2.440 inches

Furnished Items And Quantity:

Mtg hdw 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

1000.0 ohms per volt

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-5.0 to 5.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.687 inches

Meter Body Diameter Behind Mounting Flange:

2.210 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 25.0 volts, ac single indicator single range

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Phase:

Single

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Style Designator:

Round flush mtg

Supplementary Features:

Rectifier type

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0