## NSN 6625-00-450-2066

Voltmeter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-00-450-2066

Scale Division Quantity:  10 single indicator single range  Distance Between Mounting Facility Centers:  2.938 inches  Installation Design:  Panel  Mounting Arrangement Style:  Two hole/stud  Sensitivity Rating:  1000.0 ohms per volt  Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:  -3.0/+3.0 at full scale single indicator all ranges  Movement Type:  Moving iron vane  Background Color:  White single indicator single range  Power Source:  External  Measurement Range:  +0.0/+150.0 volts, ac single indicator single range  Scale Selection Method:  Terminal  Features Provided:  Magnetic shield  Movement Suspension Method:  Taut band  Circuit Attachment Method And Quantity:  2 solder stud  Material:  Plastic phenolic  Shelf Life:  N/a
Distance Between Mounting Facility Centers: 2.938 inches Installation Design: Panel Mounting Arrangement Style: Two hole/stud Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -3.0/+3.0 at full scale single indicator all ranges Movement Type: Moving iron vane Background Color: White single indicator single range Power Source: External Measurement Range: +0.0/+150.0 volts, ac single indicator single range Scale Selection Method: Terminal Features Provided: Magnetic shield Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 solder stud Material: Plastic phenolic Shelf Life:
2.938 inches Installation Design: Panel Mounting Arrangement Style: Two hole/stud Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -3.0/+3.0 at full scale single indicator all ranges Movement Type: Moving iron vane Background Color: White single indicator single range Power Source: External Measurement Range: +0.0/+150.0 volts, ac single indicator single range Scale Selection Method: Terminal Features Provided: Magnetic shield Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 solder stud Material: Plastic phenolic Shelf Life:
Installation Design: Panel  Mounting Arrangement Style: Two hole/stud  Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -3.0/+3.0 at full scale single indicator all ranges Movement Type: Moving iron vane Background Color: White single indicator single range Power Source: External Measurement Range: +0.0/+150.0 volts, ac single indicator single range Scale Selection Method: Terminal Features Provided: Magnetic shield Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 solder stud Material: Plastic phenolic Shelf Life:
Mounting Arrangement Style: Two hole/stud Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -3.0/+3.0 at full scale single indicator all ranges Movement Type: Moving iron vane Background Color: White single indicator single range Power Source: External Measurement Range: +0.0/+150.0 volts, ac single indicator single range Scale Selection Method: Terminal Features Provided: Magnetic shield Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 solder stud Material: Plastic phenolic Shelf Life:
Mounting Arrangement Style: Two hole/stud Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -3.0/+3.0 at full scale single indicator all ranges Movement Type: Moving iron vane Background Color: White single indicator single range Power Source: External Measurement Range: +0.0/+150.0 volts, ac single indicator single range Scale Selection Method: Terminal Features Provided: Magnetic shield Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 solder stud Material: Plastic phenolic Shelf Life:
Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -3.0/+3.0 at full scale single indicator all ranges Movement Type: Moving iron vane Background Color: White single indicator single range Power Source: External Measurement Range: +0.0/+150.0 volts, ac single indicator single range Scale Selection Method: Terminal Features Provided: Magnetic shield Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 solder stud Material: Plastic phenolic Shelf Life:
Sensitivity Rating: 1000.0 ohms per volt Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -3.0/+3.0 at full scale single indicator all ranges Movement Type: Moving iron vane Background Color: White single indicator single range Power Source: External Measurement Range: +0.0/+150.0 volts, ac single indicator single range Scale Selection Method: Terminal Features Provided: Magnetic shield Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 solder stud Material: Plastic phenolic Shelf Life:
Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -3.0/+3.0 at full scale single indicator all ranges Movement Type: Moving iron vane Background Color: White single indicator single range Power Source: External Measurement Range: +0.0/+150.0 volts, ac single indicator single range Scale Selection Method: Terminal Features Provided: Magnetic shield Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 solder stud Material: Plastic phenolic Shelf Life:
Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent: -3.0/+3.0 at full scale single indicator all ranges  Movement Type:  Moving iron vane  Background Color:  White single indicator single range  Power Source:  External  Measurement Range: +0.0/+150.0 volts, ac single indicator single range  Scale Selection Method:  Terminal  Features Provided:  Magnetic shield  Movement Suspension Method:  Taut band  Circuit Attachment Method And Quantity: 2 solder stud  Material:  Plastic phenolic  Shelf Life:
Black single indicator single range  Accuracy In Percent: -3.0/+3.0 at full scale single indicator all ranges  Movement Type: Moving iron vane  Background Color: White single indicator single range  Power Source: External  Measurement Range: +0.0/+150.0 volts, ac single indicator single range  Scale Selection Method: Terminal  Features Provided: Magnetic shield  Movement Suspension Method: Taut band  Circuit Attachment Method And Quantity: 2 solder stud  Material: Plastic phenolic  Shelf Life:
Accuracy In Percent: -3.0/+3.0 at full scale single indicator all ranges Movement Type: Moving iron vane Background Color: White single indicator single range Power Source: External Measurement Range: +0.0/+150.0 volts, ac single indicator single range Scale Selection Method: Terminal Features Provided: Magnetic shield Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 solder stud Material: Plastic phenolic Shelf Life:
-3.0/+3.0 at full scale single indicator all ranges  Movement Type:  Moving iron vane  Background Color:  White single indicator single range  Power Source:  External  Measurement Range: +0.0/+150.0 volts, ac single indicator single range  Scale Selection Method:  Terminal  Features Provided:  Magnetic shield  Movement Suspension Method:  Taut band  Circuit Attachment Method And Quantity: 2 solder stud  Material:  Plastic phenolic  Shelf Life:
Movement Type:  Moving iron vane  Background Color:  White single indicator single range  Power Source:  External  Measurement Range: +0.0/+150.0 volts, ac single indicator single range  Scale Selection Method:  Terminal  Features Provided:  Magnetic shield  Movement Suspension Method:  Taut band  Circuit Attachment Method And Quantity: 2 solder stud  Material:  Plastic phenolic  Shelf Life:
Moving iron vane  Background Color: White single indicator single range Power Source: External Measurement Range: +0.0/+150.0 volts, ac single indicator single range Scale Selection Method: Terminal Features Provided: Magnetic shield Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 solder stud Material: Plastic phenolic Shelf Life:
Background Color: White single indicator single range Power Source: External Measurement Range: +0.0/+150.0 volts, ac single indicator single range Scale Selection Method: Terminal Features Provided: Magnetic shield Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 solder stud Material: Plastic phenolic Shelf Life:
White single indicator single range  Power Source:  External  Measurement Range: +0.0/+150.0 volts, ac single indicator single range  Scale Selection Method:  Terminal  Features Provided:  Magnetic shield  Movement Suspension Method:  Taut band  Circuit Attachment Method And Quantity: 2 solder stud  Material:  Plastic phenolic  Shelf Life:
Power Source:  External  Measurement Range: +0.0/+150.0 volts, ac single indicator single range Scale Selection Method: Terminal Features Provided: Magnetic shield Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 solder stud Material: Plastic phenolic Shelf Life:
External  Measurement Range: +0.0/+150.0 volts, ac single indicator single range Scale Selection Method: Terminal Features Provided: Magnetic shield Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 solder stud Material: Plastic phenolic Shelf Life:
Measurement Range: +0.0/+150.0 volts, ac single indicator single range Scale Selection Method: Terminal Features Provided: Magnetic shield Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 solder stud Material: Plastic phenolic Shelf Life:
+0.0/+150.0 volts, ac single indicator single range Scale Selection Method: Terminal Features Provided: Magnetic shield Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 solder stud Material: Plastic phenolic Shelf Life:
Scale Selection Method: Terminal Features Provided: Magnetic shield Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 solder stud Material: Plastic phenolic Shelf Life:
Terminal  Features Provided:  Magnetic shield  Movement Suspension Method:  Taut band  Circuit Attachment Method And Quantity: 2 solder stud  Material:  Plastic phenolic  Shelf Life:
Features Provided: Magnetic shield Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 solder stud Material: Plastic phenolic Shelf Life:
Magnetic shield  Movement Suspension Method:  Taut band  Circuit Attachment Method And Quantity:  2 solder stud  Material:  Plastic phenolic  Shelf Life:
Movement Suspension Method: Taut band Circuit Attachment Method And Quantity: 2 solder stud Material: Plastic phenolic Shelf Life:
Taut band  Circuit Attachment Method And Quantity: 2 solder stud  Material: Plastic phenolic  Shelf Life:
Circuit Attachment Method And Quantity: 2 solder stud  Material: Plastic phenolic  Shelf Life:
2 solder stud  Material:  Plastic phenolic  Shelf Life:
Material: Plastic phenolic Shelf Life:
Plastic phenolic Shelf Life:
Shelf Life:
N/a
17/4
Unit Of Measure:
Demilitarization:
<b>Demilitarization:</b> Yes - demil/mli

A310a0