

View Online at <https://aerobasegroup.com/nsn/6625-00-455-6768>

Overall Length:

19.000 inches

Overall Height:

7.000 inches

Overall Width:

17.500 inches

Ac Voltage Rating:

Between 90.0 volts and 136.0 volts and 180.0 volts and 272.0 volts

Frequency Rating:

Between 48.0 hertz and 440.0 hertz

Frequency Range Rating:

+0.010/+40.000 gigahertz

Furnished Items And Quantity:

6 ft bnc cable, 50 ohm miniature coax-1.6 ft n cable, rg 223/u coax-1, 2 ft tnc cable, rg223/u coax-1, 12.4 to 18 ghz wave guide mixer-1; 18 to 26.5 ghz wave guide mixer-1; 26.5 to 40.0 ghz wave guide mixer-1; 20 db attenuator-1; 40 db attenuator-1; bnc male to n female adapters-2; bnc female to n male adapters-2; wave guide mixer adapter-1; power cord-1; 3 to 2 wire adapter-1; blue light filter-1; clear crt protector plate-1; ornamental ring-1; mesh filter-1; one ampere fuses-2; 1/2 ampere fuse-1; front cover-1; instructional manual-2

Input Impedance Rating:

50.0 ohms

Frequency Band Quantity:

8

Frequency Channel Quantity:

8

Individual Channel Frequency:

Between 10.0 megahertz and 275.0 megahertz and 275.0 megahertz and 900.0 megahertz and 2.0 megahertz and 800.0 gigahertz and 1.5 gigahertz and 4.0 gigahertz and 3.8 gigahertz and 8.2 gigahertz and 8.2 gigahertz and 12.4 gigahertz and 12.4 gigahertz and 18.0 gigahertz and 18.0 gigahertz and 40.0 gigahertz

Unit Type:

Standard

Frequency Calibration Accuracy Range In Percent:

-3.0/+3.0

Mounting Method:

Rack

Cathode Ray Tube Displayed Information:

Frequency differences

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A532n0