NSN 6625-00-456-3120

Range Indicator Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-456-3120

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.850 inches

Mounting Hole Diameter:

Between 0.143 inches and 0.157 inches

Scale Division Quantity:

60 single indicator single range

Overall Diameter:

3.510 inches

Environmental Protection:

Shock resistant and vibration resistant and watertight

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Mtg hdw 3; term. Hdw 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

1.660 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

NSN 6625-00-456-3120

Range Indicator Meter - Page 2 of 2



Scale Graduation Type:
Linear single indicator single range
Measurement Range:
-1500.0 to 1500.0 yards single indicator single range
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Special Features:
Ruggedized
Special Markings:
Minus sign above scale and to the left; plus sign above scale and to the right
Material:
Stainless steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel semigloss
Special Test Features:
Conforms to mil-m-10304/12
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Fiig:
A310a0