

View Online at <https://aerobasegroup.com/nsn/6625-00-456-7444>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

1.251 inches

**Overall Diameter:**

Between 1.235 inches and 1.265 inches

**Environmental Protection:**

Humidity resistant and shock resistant and vibration resistant and watertight

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Sensitivity Rating:**

100.0 microamperes

**Dial Scale Marking Color:**

Green and red single indicator single range

**Accuracy In Percent:**

-3.0 to 3.0 at full scale single indicator single range

**Unable To Decode:**

Unable to decode or unable to decode

**Meter Depth Behind Mounting Flange:**

0.375 inches

**Meter Body Diameter Behind Mounting Flange:**

Between 0.985 inches and 1.000 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Scale Marking:**

L side of scale to 0 ua deflection colored red; 20 to 50 ua deflection colored green; 100 ua to r side of scale colored red

**Mounting Facility Type And Quantity:**

1 threaded body and 1 threaded ring

**Scale Graduation Type:**

Nonlinear single indicator single range

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder lug

**Special Features:**

Ruggedized

**Material:**

Steel

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0