

View Online at <https://aerobasegroup.com/nsn/6625-00-456-7444>

Circuit Current For Which Designed:

Dc

Overall Length:

1.251 inches

Overall Diameter:

Between 1.235 inches and 1.265 inches

Environmental Protection:

Humidity resistant and shock resistant and vibration resistant and watertight

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

100.0 microamperes

Dial Scale Marking Color:

Green and red single indicator single range

Accuracy In Percent:

-3.0 to 3.0 at full scale single indicator single range

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

0.375 inches

Meter Body Diameter Behind Mounting Flange:

Between 0.985 inches and 1.000 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

L side of scale to 0 ua deflection colored red; 20 to 50 ua deflection colored green; 100 ua to r side of scale colored red

Mounting Facility Type And Quantity:

1 threaded body and 1 threaded ring

Scale Graduation Type:

Nonlinear single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0