

View Online at <https://aerobasegroup.com/nsn/6625-00-457-1048>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

1.312 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

Between 1.307 inches and 1.317 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

Between 1.307 inches and 1.317 inches

**Overall Height:**

1.766 inches

**Overall Width:**

1.766 inches

**Environmental Protection:**

Shock resistant and vibration resistant

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

200.0 microamperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-3.0 to 3.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

0.843 inches

**Meter Body Diameter Behind Mounting Flange:**

1.497 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Power Source:**

External

**Scale Graduation Type:**

Nonlinear single indicator single range

**Measurement Range:**

-20.0 to 3.0 decibels single indicator single range

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 solder lug

**Material:**

Aluminum

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0