

View Online at <https://aerobasegroup.com/nsn/6625-00-458-2481>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

2.276 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 5.240 inches and 5.260 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 2.090 inches and 3.010 inches

Overall Height:

Between 4.318 inches and 4.348 inches

Overall Width:

Between 5.602 inches and 5.622 inches

Scale Division Quantity:

61 single indicator 2nd range

Mounting Stud Length:

0.500 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Furnished Items And Quantity:

Nut 8; lockwasher 6; shunt wire 1; seal 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

100.0 volts

Dial Scale Marking Color:

Red single indicator 3rd range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Unable To Decode:

Unable to decode or unable to decode

Meter Depth Behind Mounting Flange:

Between 1.155 inches and 1.165 inches

Meter Body Diameter Behind Mounting Flange:

Between 2.770 inches and 2.790 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Red single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Nonlinear single indicator 3rd range

Measurement Range:

+0.0 to 50.0 millivolts, ac single indicator 3rd range

Mounting Stud Diameter:

Between 0.128 inches and 0.148 inches

Scale Selection Method:

Terminal

Features Provided:

External shunting and luminous scale marking and magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0