

View Online at <https://aerobasegroup.com/nsn/6625-00-458-6297>

Circuit Current For Which Designed:

Dc

Overall Length:

3.945 inches

Overall Height:

0.910 inches

Overall Width:

2.145 inches

Mounting Hole Diameter:

0.120 inches

Distance Between Mounting Facility Centers:

0.710 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.106 inches

Meter Body Width Behind Mounting Flange:

0.610 inches

Movement Type:

Moving iron vane

Mounting Facility Type And Quantity:

2 unthreaded hole

Measurement Range:

+0.0 to 500.0 milliamperes, dc single indicator single range

Meter Body Height Behind Mounting Flange:

0.710 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0