## NSN 6625-00-458-8349

Interference Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-458-8349 **Overall Length:** 1.750 inches **Overall Height:** 1.250 inches **Overall Width:** 1.750 inches **Environmental Protection:** Dustproof and electrically insulated and watertight **Vibration Resistance Range In Hertz:** Not rated **Shock Resistance Rating In Gravitational Units:** Not rated **Operating Tempurature Range:** Not rated **Average Life Rating: Average Life Measurement:** Hours **Average Life Rating In Hours:** 1000.0 **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** 80000.0 feet **Inclosure Type:** Encased **Operating Control Method:** Automatic Installation Design: Mechanical **Control Type:** Remote **Circuit Construction Type:** Solid state Frequency Per Channel: 30.0 hertz operating channel **Frequency Adjustment Type:** Continuous **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:** 

Not rated

## NSN 6625-00-458-8349

Interference Generator - Page 2 of 2



Signal Voltage Rating Per Channel:
Not rated
Overall Gain:
Not rated
Impedance Rating Per Channel:
600.000 ohms output channel
Pulse Peak Amplitude Per Channel:
Not rated
Interference Pattern:
Random pulsed noise
Maximum Continuous Operating Time In Hours:
Not rated
External Dc Operating Voltage In Volts:
22.5 single voltage
Special Test Features:
Mil-q-21549b-sp24-1
Fsc Application Data:
Ranging set, sonar
Reference Number Differentiating Characteristics:
As differentiated by special test features
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A32200
Mil-std (military Standard):
Mil-q-21549 spec.