

View Online at <https://aerobasegroup.com/nsn/6625-00-464-2964>

**Overall Length:**

20.500 inches

**Overall Height:**

7.000 inches

**Overall Width:**

19.000 inches

**Current Type:**

Ac

**Frequency Rating:**

Between 60.0 hertz and 400.0 hertz

**Voltage Rating:**

Between 90.0 volts and 110.0 volts and 104.0 volts and 126.0 volts and 112.0 volts and 136.0 volts and 180.0 volts and 220.0 volts and 208.0 volts and 252.0 volts and 224.0 volts and 272.0 volts

**Beam Quantity:**

1

**Mounting Method:**

Rack

**Screen Size:**

5.000 in.

**Sweep Circuits:**

Not included

**Amplifier Deflection Sensitivity Provision:**

Not provided

**Input Intensity Modulation Feature:**

Not provided

**Plate Direct Connection Deflection Sensitivity Provision:**

Not provided

**Frequency Response Rating:**

Not provided

**Amplifier Input Impedance Rating Provision:**

Not provided

**Calibrated Screen Scale:**

Not included

**Trace Storage Tube:**

Not included

**Plug In Unit Function And Quantity:**

20 amplifiers

**Camera Recording Device Accommodation:**

Not provided

**Phase:**

Single

**Functional Classification:**

Aa-3.2

**Functional Description:**

May be used with different plug-in units providing versatility in measurement applications. Has independent vertical and horizontal systems. Dual plug-in feature allows conventional displays or x-y displays weither single -trace, dual trace, or four trace units. Accepts all 2-series and 3-series amplifier and time base units except type 3s6 & type 3t6 plug-ins. Solid state except for crt tube

**Entry Date:**

73-12-01

**Reference Data And Literature:**

T.O. 33a1-13-399-1

**Relationship To Similar Equipment:**

INTE-RC-HAN-GEAB

**Fsc Application Data:**

Oscilloscopes, except specially designed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T320-g