

View Online at <https://aerobasegroup.com/nsn/6625-00-465-6945>

Circuit Current For Which Designed:

Dc

Overall Length:

1.867 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.875 inches

Overall Height:

4.641 inches

Overall Width:

5.746 inches

Scale Division Quantity:

60 single indicator 1st range

Mounting Stud Length:

0.500 inches

Furnished Items And Quantity:

Nut 4; washer 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.330 inches

Meter Body Diameter Behind Mounting Flange:

2.780 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

Black single indicator all ranges and white single indicator all ranges

Pointer Color:

Red single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0/+3.0 amperes, dc single indicator 1st range

Mounting Stud Diameter:

0.138 inches

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 turret

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0