NSN 6625-00-466-2069

Ammeter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-00-466-2069

Circuit Current For Which Designed:
Ac
Overall Length:
0.850 inches
Overall Diameter:
2.200 inches
Distance Between Mounting Facility Centers:
1.000 inches
Installation Design:
Panel
Mounting Arrangement Style:
Two hole/stud
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
0.690 inches
Meter Body Diameter Behind Mounting Flange:
2.030 inches
Movement Type:
Movement Type: Electrodynamometer
Electrodynamometer
Electrodynamometer Background Color:
Electrodynamometer Background Color: White single indicator single range
Electrodynamometer Background Color: White single indicator single range Mounting Facility Type And Quantity:
Electrodynamometer Background Color: White single indicator single range Mounting Facility Type And Quantity: 2 bracket
Electrodynamometer Background Color: White single indicator single range Mounting Facility Type And Quantity: 2 bracket Measurement Range:
Electrodynamometer Background Color: White single indicator single range Mounting Facility Type And Quantity: 2 bracket Measurement Range: -60.0/+60.0 amperes, ac single indicator single range
Electrodynamometer Background Color: White single indicator single range Mounting Facility Type And Quantity: 2 bracket Measurement Range: -60.0/+60.0 amperes, ac single indicator single range Circuit Attachment Method And Quantity:
Electrodynamometer Background Color: White single indicator single range Mounting Facility Type And Quantity: 2 bracket Measurement Range: -60.0/+60.0 amperes, ac single indicator single range Circuit Attachment Method And Quantity: 2 binding post
Electrodynamometer Background Color: White single indicator single range Mounting Facility Type And Quantity: 2 bracket Measurement Range: -60.0/+60.0 amperes, ac single indicator single range Circuit Attachment Method And Quantity: 2 binding post Style Designator:
Electrodynamometer Background Color: White single indicator single range Mounting Facility Type And Quantity: 2 bracket Measurement Range: -60.0/+60.0 amperes, ac single indicator single range Circuit Attachment Method And Quantity: 2 binding post Style Designator: Round flush mtg
Electrodynamometer Background Color: White single indicator single range Mounting Facility Type And Quantity: 2 bracket Measurement Range: -60.0/+60.0 amperes, ac single indicator single range Circuit Attachment Method And Quantity: 2 binding post Style Designator: Round flush mtg Shelf Life:
Electrodynamometer Background Color: White single indicator single range Mounting Facility Type And Quantity: 2 bracket Measurement Range: -60.0/+60.0 amperes, ac single indicator single range Circuit Attachment Method And Quantity: 2 binding post Style Designator: Round flush mtg Shelf Life: N/a
Electrodynamometer Background Color: White single indicator single range Mounting Facility Type And Quantity: 2 bracket Measurement Range: -60.0/+60.0 amperes, ac single indicator single range Circuit Attachment Method And Quantity: 2 binding post Style Designator: Round flush mtg Shelf Life: N/a
Electrodynamometer Background Color: White single indicator single range Mounting Facility Type And Quantity: 2 bracket Measurement Range: -60.0/+60.0 amperes, ac single indicator single range Circuit Attachment Method And Quantity: 2 binding post Style Designator: Round flush mtg Shelf Life: N/a Unit Of Measure:
Electrodynamometer Background Color: White single indicator single range Mounting Facility Type And Quantity: 2 bracket Measurement Range: -60.0/+60.0 amperes, ac single indicator single range Circuit Attachment Method And Quantity: 2 binding post Style Designator: Round flush mtg Shelf Life: N/a Unit Of Measure: Demilitarization: