NSN 6625-00-470-7447

Ammeter - Page 1 of 2

Dc

Overall Length: 2.690 inches

0.880 inches

Scale Division Quantity:

Mounting Stud Length:

60 single indicator single range

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-470-7447

Overall Diameter:
2.300 inches
Distance Between Mounting Facility Centers:
1.250 inches
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Two hole/stud
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-3.0/+3.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
2.420 inches
Meter Body Diameter Behind Mounting Flange:
2.060 inches
Movement Types
Movement Type:
Moving coil, permanent magnet
Moving coil, permanent magnet
Moving coil, permanent magnet Background Color:
Moving coil, permanent magnet Background Color: White single indicator single range
Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color:
Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: Black single indicator single range
Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: Black single indicator single range Mounting Facility Type And Quantity:
Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: Black single indicator single range Mounting Facility Type And Quantity: 2 threaded stud
Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: Black single indicator single range Mounting Facility Type And Quantity: 2 threaded stud Scale Graduation Type:
Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: Black single indicator single range Mounting Facility Type And Quantity: 2 threaded stud Scale Graduation Type: Linear single indicator single range
Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: Black single indicator single range Mounting Facility Type And Quantity: 2 threaded stud Scale Graduation Type: Linear single indicator single range Measurement Range:
Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: Black single indicator single range Mounting Facility Type And Quantity: 2 threaded stud Scale Graduation Type: Linear single indicator single range Measurement Range: -60.0/+60.0 amperes, dc single indicator single range
Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: Black single indicator single range Mounting Facility Type And Quantity: 2 threaded stud Scale Graduation Type: Linear single indicator single range Measurement Range: -60.0/+60.0 amperes, dc single indicator single range Mounting Stud Diameter:
Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: Black single indicator single range Mounting Facility Type And Quantity: 2 threaded stud Scale Graduation Type: Linear single indicator single range Measurement Range: -60.0/+60.0 amperes, dc single indicator single range Mounting Stud Diameter: 0.169 inches
Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: Black single indicator single range Mounting Facility Type And Quantity: 2 threaded stud Scale Graduation Type: Linear single indicator single range Measurement Range: -60.0/+60.0 amperes, dc single indicator single range Mounting Stud Diameter: 0.169 inches Features Provided:

NSN 6625-00-470-7447

Ammeter - Page 2 of 2



Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, electronic equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A310a0