NSN 6625-00-471-0555

Voltmeter - Page 1 of 2

Circuit Current For Which Designed:

Dielectric Withstanding Voltage In Volts:



View Online at https://aerobasegroup.com/nsn/6625-00-471-0555

3000.0
Overall Length:
2.060 inches
Scale Division Quantity:
100 single indicator single range
Mounting Stud Length:
0.500 inches
Overall Diameter:
3.510 inches
Mounting Bolt Circle Diameter:
3.160 inches
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
1000.0 ohms per volt
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-1.0/+1.0 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
1.660 inches
1.660 inches Meter Body Diameter Behind Mounting Flange:
Meter Body Diameter Behind Mounting Flange:
Meter Body Diameter Behind Mounting Flange: 2.800 inches
Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color:
Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range
Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity:
Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud
Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range:
Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +0.0/+500.0 volts, dc single indicator single range
Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +0.0/+500.0 volts, dc single indicator single range Mounting Stud Diameter:
Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +0.0/+500.0 volts, dc single indicator single range Mounting Stud Diameter: 0.138 inches
Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +0.0/+500.0 volts, dc single indicator single range Mounting Stud Diameter: 0.138 inches Circuit Attachment Method And Quantity:
Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +0.0/+500.0 volts, dc single indicator single range Mounting Stud Diameter: 0.138 inches Circuit Attachment Method And Quantity: 2 binding post
Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +0.0/+500.0 volts, dc single indicator single range Mounting Stud Diameter: 0.138 inches Circuit Attachment Method And Quantity: 2 binding post Material:
Meter Body Diameter Behind Mounting Flange: 2.800 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 threaded stud Measurement Range: +0.0/+500.0 volts, dc single indicator single range Mounting Stud Diameter: 0.138 inches Circuit Attachment Method And Quantity: 2 binding post Material: Steel

NSN 6625-00-471-0555

Voltmeter - Page 2 of 2



Sty				

Round flush mtg

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0