

View Online at <https://aerobasegroup.com/nsn/6625-00-471-8969>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1500.0

Overall Length:

3.700 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.406 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.718 inches

Overall Height:

1.000 inches

Overall Width:

2.690 inches

Mounting Hole Diameter:

0.140 inches

Scale Division Quantity:

18 single indicator all ranges

Environmental Protection:

Cold resistant and heat resistant and shock resistant and submersible and vibration resistant and watertight

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

500.0 microamperes

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

2.500 inches

Meter Body Width Behind Mounting Flange:

2.100 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

-9.0 to 9.0 volts, dc single indicator 1st range

Scale Selection Method:

Terminal

Meter Body Height Behind Mounting Flange:

1.000 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular semi-flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0