

View Online at <https://aerobasegroup.com/nsn/6625-00-471-8979>

Circuit Current For Which Designed:

Dc

Overall Length:

3.685 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.376 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.376 inches

Overall Height:

4.300 inches

Overall Width:

4.300 inches

Scale Division Quantity:

100 single indicator single range

Mounting Stud Length:

0.500 inches

Furnished Items And Quantity:

Shunt 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

3.060 inches

Meter Body Diameter Behind Mounting Flange:

3.970 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+2.0 amperes, dc single indicator single range

Mounting Stud Diameter:

0.250 inches

Features Provided:

Magnetic shield

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 binding post

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Specification Data:

30003-68a75c39 manufacturers source control

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0