

View Online at <https://aerobasegroup.com/nsn/6625-00-472-2018>

Overall Length:

15.875 inches

Overall Height:

6.000 inches

Overall Width:

9.000 inches

Vibration Resistance Range In Hertz:

Not rated

Shock Resistance Rating In Gravitational Units:

Not rated

Operating Temperature Range:

+20.0 to 30.0 degrees celsius

Average Life Measurement:

Not rated

Basic Shape Style:

Rectangular or square

Inclosure Type:

Encased

Operating Control Method:

Manual

Installation Design:

Portable

Control Type:

Local

Circuit Construction Type:

Solid state

Frequency Adjustment Type:

Continuous

Attenuation In Decibels:

Not rated

Average Power Rating Per Channel:

Not rated

Signal Voltage Rating Per Channel:

2.000 volts input and 20.000 volts input

Overall Gain:

Not rated

Impedance Rating Per Channel:

50.000 ohms output channel

Pulse Rise Time Per Channel:

10.000 nanoseconds output channel

Pulse Decay Time Per Channel:

100.000 microseconds output channel

Pulse Peak Amplitude Per Channel:

20.000 volts output channel

Pulse Modulation Type Per Channel:

Amplitude input channel

Signal Data Type Per Channel:

Input channel pulse

Output Wave Shape:

Pulse, trigger

Indicator Device Type And Quantity:

1 cathode ray tube

Maximum Continuous Operating Time In Hours:

Not rated

Operating Ac Frequency In Hertz:

66.0 single voltage

Calibration Function:

Frequency and pulse duration and pulse repetition

External Ac Operating Voltage In Volts:

90.0 1st voltage

Functional Classification:

Bb-1.1

Entry Date:

91-02-19

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A32200