NSN 6625-00-472-7853

Special Scale Meter - Page 1 of 2

Circuit Current For Which Designed:

Dc

Overall Length:



View Online at https://aerobasegroup.com/nsn/6625-00-472-7853

| 2.820 inches |
|---|
| Mounting Hole Diameter: |
| 0.150 inches |
| Scale Division Quantity: |
| 100 single indicator single range |
| Overall Diameter: |
| 3.510 inches |
| Environmental Protection: |
| Shock resistant and vibration resistant |
| Mounting Bolt Circle Diameter: |
| 3.160 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Sensitivity Rating: |
| 200.0 microamperes |
| Dial Scale Marking Color: |
| S . |
| Black single indicator single range |
| · |
| Black single indicator single range |
| Black single indicator single range Accuracy In Percent: |
| Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range |
| Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: |
| Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.420 inches |
| Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.420 inches Meter Body Diameter Behind Mounting Flange: |
| Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.420 inches Meter Body Diameter Behind Mounting Flange: 2.800 inches |
| Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.420 inches Meter Body Diameter Behind Mounting Flange: 2.800 inches Movement Type: |
| Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.420 inches Meter Body Diameter Behind Mounting Flange: 2.800 inches Movement Type: Moving coil, permanent magnet |
| Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.420 inches Meter Body Diameter Behind Mounting Flange: 2.800 inches Movement Type: Moving coil, permanent magnet Background Color: |
| Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.420 inches Meter Body Diameter Behind Mounting Flange: 2.800 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range |
| Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.420 inches Meter Body Diameter Behind Mounting Flange: 2.800 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: |
| Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.420 inches Meter Body Diameter Behind Mounting Flange: 2.800 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: Black single indicator single range |
| Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.420 inches Meter Body Diameter Behind Mounting Flange: 2.800 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: Black single indicator single range Scale Marking: |
| Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 2.420 inches Meter Body Diameter Behind Mounting Flange: 2.800 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color: Black single indicator single range Scale Marking: 0; 5; 10; 15; 20; feet |

Linear single indicator single range

NSN 6625-00-472-7853

Special Scale Meter - Page 2 of 2



| Features Provided: | |
|---|--|
| Zero adjuster | |
| Movement Suspension Method: | |
| Jewel pivot base | |
| Circuit Attachment Method And Quantity: | |
| 2 screw and 2 solder lug | |
| Special Features: | |
| Ruggedized | |
| Material: | |
| Steel | |
| Nuclear Hardness Critical Feature: | |
| Nonhardened | |
| Style Designator: | |
| Round flush mtg | |
| Fsc Application Data: | |
| Test set, elect. Equip. | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A310a0 | |
| | |