

View Online at <https://aerobasegroup.com/nsn/6625-00-477-6287>

Circuit Current For Which Designed:

Dc

Overall Length:

2.350 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 2.102 inches and 2.122 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 1.819 inches and 1.839 inches

Overall Height:

2.690 inches

Overall Width:

2.690 inches

Scale Division Quantity:

50 single indicator single range

Mounting Stud Length:

0.670 inches

Environmental Protection:

Shock resistant and vibration resistant

Shortest Horizontal Distance Between Mounting Centers:

Between 1.046 inches and 1.066 inches

Furnished Items And Quantity:

Nut 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud triangular

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.850 inches

Meter Body Diameter Behind Mounting Flange:

2.150 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-50.0/+50.0 microamperes, dc single indicator single range

Mounting Stud Diameter:

0.250 inches

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0