

View Online at <https://aerobasegroup.com/nsn/6625-00-478-6438>

Circuit Current For Which Designed:

Dc

Overall Length:

1.625 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

Between 1.306 inches and 1.318 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

Between 1.306 inches and 1.318 inches

Overall Height:

Between 1.734 inches and 1.766 inches

Overall Width:

Between 1.734 inches and 1.766 inches

Mounting Hole Diameter:

Between 0.120 inches and 0.130 inches

Environmental Protection:

Shock resistant and vibration resistant

Furnished Items And Quantity:

Screw 4; nut 4; lockwasher 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

5.0 microamperes and 25.0 microamperes

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.000 inches

Meter Body Diameter Behind Mounting Flange:

1.510 inches

Movement Type:

Moving coil, permanent magnet

Pointer Color:

White single indicator single range

Scale Marking:

Zero to 30

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Conforms to mil-m-10304

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0