

View Online at <https://aerobasegroup.com/nsn/6625-00-479-3640>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

2000.0

Overall Length:

1.710 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

5.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.000 inches

Overall Height:

4.490 inches

Overall Width:

5.620 inches

Scale Division Quantity:

30 single indicator single range

Mounting Stud Length:

0.510 inches

Furnished Items And Quantity:

Thermocupler 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Frequency Response Range:

+14.000/+32.000 kilohertz

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0/+1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

0.560 inches

Meter Body Diameter Behind Mounting Flange:

3.125 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0/+400.0 amperes, rf single indicator single range

Mounting Stud Diameter:

0.167 inches

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0