

View Online at <https://aerobasegroup.com/nsn/6625-00-481-3913>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

2000.0

Overall Length:

5.297 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.822 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.900 inches

Overall Height:

1.500 inches

Overall Width:

5.062 inches

Mounting Hole Diameter:

Between 0.123 inches and 0.133 inches

Scale Division Quantity:

25 single indicator single range

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

4.141 inches

Meter Body Width Behind Mounting Flange:

4.531 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

-25.0/+25.0 milliamperes, dc single indicator single range

Meter Body Height Behind Mounting Flange:

0.906 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 binding post

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0