

View Online at <https://aerobasegroup.com/nsn/6625-00-481-4397>

Circuit Current For Which Designed:

Ac

Overall Length:

2.053 inches

Overall Height:

3.500 inches

Overall Width:

3.500 inches

Scale Division Quantity:

75 single indicator single range

Frequency Rating:

400.0 hertz

Mounting Stud Length:

0.500 inches

Environmental Protection:

Water resistant

Mounting Bolt Circle Diameter:

2.760 inches

Furnished Items And Quantity:

Gasket 1; mtg hdw 3; term.Hdw 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.303 inches

Meter Body Diameter Behind Mounting Flange:

2.794 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 150.0 volts, ac single indicator single range

Mounting Stud Diameter:

0.138 inches

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Supplementary Features:

Terminal resistance: 15000 ohms; overload: 20 percent; insulation level: 2600 volts rms; response time: 2.5 seconds

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0