

View Online at <https://aerobasegroup.com/nsn/6625-00-481-9899>

Overall Length:

20.625 inches

Overall Height:

13.750 inches

Overall Width:

9.750 inches

Current Type:

Ac

Frequency Rating:

60.0 hertz

Voltage Rating:

Between 105.0 volts and 125.0 volts and 210.0 volts and 250.0 volts

Beam Quantity:

1

Mounting Method:

Table

Accuracy Range In Percent:

-1.0/+1.0 or -2.5/+2.5

Screen Size:

6 by 10 centimeters

Sweep Circuits:

Included

Generator Driven Feature:

Included

Sweep Circuit Type:

Horizontal and vertical

Sweep Frequency Range:

+0.000/+50.000 megahertz

Trigger Sweep Polarity Switch:

Included

Expanded Sweep:

Provided

Amplifier Deflection Sensitivity Provision:

Provided

Vertical Deflection Sensitivity Voltage Rating:

10.0 millivolts peak to peak per centimeter and 100.0 millivolts peak to peak per centimeter

Horizontal Deflection Sensitivity Voltage Rating:

0.1 volts cw megahertz and 1.0 volts peak megahertz

Plate Direct Connection Deflection Sensitivity Provision:

Provided

Direct Connection Vertical Deflection Sensitivity Voltage Rating:

10.0 volts cw megahertz and 15.0 volts peak megahertz

Direct Connection Horizontal Deflection Sensitivity Voltage Rating:

5.2 volts peak to peak per centimeter and 7.2 volts peak to peak per centimeter

Amplifier Input Impedance Rating Provision:

Provided

X-axis Input Impedance Rating:

1.0 megohms

Y-axis Input Impedance Rating:

1.0 megohms

Z-axis Input Impedance Rating:

1.0 megohms

Amplitude Calibrating Voltage Waveform:

Square wave

Calibrating Peak To Peak Amplitude:

1.0 volts

Plug In Unit Function And Quantity:

Vertical amplifier1 and horizontal amplifier

Camera Recording Device Accommodation:

Not provided

Phase:

Single

Special Features:

Single or duel trace to vertical plug-in

Reference Data And Literature:

To 33a1-13-419-1

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T320-g