

View Online at <https://aerobasegroup.com/nsn/6625-00-482-8636>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

500.0

Overall Length:

4.280 inches

Overall Height:

Between 0.490 inches and 0.510 inches

Overall Width:

Between 3.990 inches and 4.010 inches

Mounting Hole Diameter:

Between 0.175 inches and 0.185 inches

Distance Between Mounting Facility Centers:

3.560 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Two hole/stud

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

Between 3.400 inches and 3.700 inches

Meter Body Width Behind Mounting Flange:

Between 2.840 inches and 3.040 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Red single indicator single range

Scale Marking:

Opening; closing; 30, 20, 10, 5, 0, 5, 10, 20, 30

Mounting Facility Type And Quantity:

2 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Meter Body Height Behind Mounting Flange:

Between 0.490 inches and 0.510 inches

Features Provided:

Self-illumination facility

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

4 threaded stud

Special Markings:

Term. Marked 1, 2, +, -

Material:

Aluminum alloy

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Anodize

Style Designator:

Rectangular semi-flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0