NSN 6625-00-489-0583

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-489-0583

| Circuit Current For Which Designed: | | | | |
|---|--|--|--|--|
| Dc | | | | |
| Overall Length: | | | | |
| 1.310 inches | | | | |
| Scale Division Quantity: | | | | |
| 100 single indicator single range | | | | |
| Overall Diameter: | | | | |
| 1.688 inches | | | | |
| Indicator Type: | | | | |
| Dial w/pointer | | | | |
| Installation Design: | | | | |
| Panel | | | | |
| Dial Scale Marking Color: | | | | |
| Black single indicator single range | | | | |
| Accuracy In Percent: | | | | |
| -5.0 to 5.0 at full scale single indicator single range | | | | |
| Meter Depth Behind Mounting Flange: | | | | |
| 0.765 inches | | | | |
| Meter Body Diameter Behind Mounting Flange: | | | | |
| Between 1.485 inches and 1.500 inches | | | | |
| Movement Type: | | | | |
| Moving coil, permanent magnet | | | | |
| Background Color: | | | | |
| White single indicator single range | | | | |
| Pointer Color: | | | | |
| Black single indicator single range | | | | |
| Power Source: | | | | |
| External | | | | |
| Mounting Facility Type And Quantity: | | | | |
| 1 ring and 1 threaded body | | | | |
| Scale Graduation Type: | | | | |
| Linear single indicator single range | | | | |
| Measurement Range: | | | | |
| +0.0 to 500.0 volts, dc single indicator single range | | | | |
| Movement Suspension Method: | | | | |
| Jewel pivot base | | | | |
| Circuit Attachment Method And Quantity: | | | | |
| 2 solderless lug | | | | |
| Nuclear Hardness Critical Feature: | | | | |
| Nonhardened | | | | |

Style Designator: Round flush mtg

NSN 6625-00-489-0583

Voltmeter - Page 2 of 2



| | Fsc | App | lication | Data: |
|--|-----|-----|----------|-------|
|--|-----|-----|----------|-------|

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A310a0